

H&B PETROLEUM COMPANY  
ROCKAWAY, NEW JERSEY  
telephone 973-664-0144  
fax 973-664-9811

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910 1200. Standard must be consulted for specific requirements.

---

Identity (As used on Label and List)

Habcool 312

---

Section I

---

Manufacturer's Name	H&B Petroleum Company
Emergency Telephone Number -	973-697-4800
Address	Telephone Number for Information
PO Bo 694	973-664-0144
Newfoundland, New Jersey 07435	
Date Prepared	Signature of Preparer (optional)
January, 2007	S D Huber

---

Section II - Hazardous Ingredients/Identity Information

---

Hazardous Components

(Specific Chemical Identity; Common Name(s))

There are no hazardous components in Habcool 312. Hazard Labeling is not required.

Habcool 312 contains: Petroleum Oil - CAS # 64742- 4- 7  
Sulphurized Hydrocarbon - CAS # 72162-15-3  
Hexylene Glycol - CAS # n/a blend

---

Section III - Physical/Chemical Characteristics

---

Boiling Point	212°F	Specific Gravity (H2O = 1)	Baume 24
Vapor Pressure (mmHg)	na	Melting Point	na
Vapor Density (Air = 1)	na	Evaporation Rate (Butyl Acetate = 1)	na
Solubility in Water	yes		
Appearance and Odor	Light yellow milky liquid - no odor.		

---

Section IV - Fire and Explosion Hazard Data

---

Flash Point (method used)	375°COC	Flammable Limits -	LEL	na	UEL	na
Extinguishing Media	CO2, dry chemical, foam					
Special Fire Fighting Procedures	none					
Unusual Fire and Explosion Hazards	none					

---

Section V - Reactivity Data

---

Stability	Unstable	Stable	X
Conditions to Avoid	na		
Incompatibility (materials to avoid)	none		

